



BORMA WACHS®

Wood Professional Cosmetics



Technical Data Sheet

Revision 00 of 20.10.2012

HARD TOP POLISH

Dab on varnish

DESCRIPTION:

Ready to use, high resistance nitro lacquer solution. Made of natural dewaxed shellac and cellulose resins. Gives high shine and softness on a protective treatment on all wooden surfaces. Indoor use. Formaldehyde free.

PHYSICAL – CHEMICAL CHARACTERISTICS:

Appearance :	liquid
Colour :	colourless
Odour :	characteristic
Dilution :	ready to use
Eventual dilution :	10 - 20 Shellac 99°
Drying time:	Over application 30 - 60 mins at 20 °C Total 3 - 6 hrs at 20°C
Dry residual:	25%
Specific weight :	0,810 Kg/Lt + 0,030
Coverage :	9-12 m ² /Lt
Temperature of application:	> 10°C
Safety indication :	highly inflammable

METHOD OF USAGE:

Apply thin layers of the product on a clean, dry surface with a small brush, or dab, or by spray. When spraying, a 13/40 nozzle at 4mbar is advisable.

Between one coat and another, make sure it is completely dry, and if necessary proceed with a light sandpapering with grain 320/400. After three applications, you can achieve an extremely shiny and soft surface.

The product can be stained with universal stain Holzfarbe.

PACKAGE:

The product comes in tins of 500ml, 1Lt, 5Lt. Also available in 400ml spray can.

STORAGE:

Keep in a fresh and well ventilated place; keep the container closed when not in use. Keep away from heat, flames, sparks and other sources of ignition. Storage time: 12months approx. if kept in the original containers.

WARNING:

Our data sheets are prepared on the basis of average performance of our tests. However, our technical advices are given in good faith but without any warranty. In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs. We will ensure the continuity of the chemical-physical characteristics.